



# Compaq NL2006

## Die-Cast Aluminium Housing



### GENERAL INFORMATION

Mounting Module	Post top or side entry from 25-45Ø Post top or side entry from 42- 60Ø Post top or side entry from 60-76Ø (optional) Spigot entry 100mm
Mounting Module Tilt Angles	Post top/side entry 0, +5,+10, +15
Operating Temperature	-40°C / +55°C
Storage Temperature	-40°C / +80°C
Glass Mounting Options	Capsule mounting system
LED Modules	Removable / Replaceable optical unit
Lens Options	COL 1030 (standard) Project-specific lens selection
Main Reference Company Standards	EN 62717, EN 62722-1, EN 62722-2-1, EN 60598-1, EN 60598-2-3, EN 62471, EN 60068-2-11, EN60068-2-52, ISO9227, ASTM B117, ASTM D3359-78, ISO 4628-2, ISO 4628-4, EN 60529, EN 62262, ANSI C136.10-2017, ANSI C136.2-2018, EN 62031, IEC 62384, ASTM D3359, EN ISO 2409, IES LM 80-15, IES LM 82-12, IES LM 84-14, IES LM 85-14, IES TM 21-11, CE, CB, RoHS, ISO9001, ISO14001, ISO18001, ISO5001, ISO45001, ISO39001, EAC, TURKAK

### HOUSING AND MATERIALS

Housing	Non corrosive high pressure die-cast aluminium
Optic	PMMA or PC
Gasket	Silicon or polyurethane without junction points.
Housing Finish	UNI EN1706 powder painted
Refractor	Tempered glass min. 4mm high transparency UV resistant (optional)
Cable Gland	IP66, Plastic PG9, IP67 (optional), IP68 (optional)
Standard Colour	RAL7021 Metallic
Tightness Level	IP66, IP67 (optional), IP68 (optional)
Impact Housing Resistance	IK10 (20 J)
Impact Glass Resistance	IK08 (5 J), IK09 (optional) (10 J), IK10 (optional) (20 J)
Vibration Test	Compliant with modified IEC 68-2-6 (0.5G), ANSI C136.31 (3G-5G)

### ELECTRICAL INFORMATION

Electrical Class	Class I, Class II (optional)
Nominal Voltage	220-240V 50 / 60 Hz EU 110-277V 50 / 60 Hz (optional) NORTH AMERICA
LED Current	350 mA, 500 mA, 600 mA, 700 mA, 800 mA 925 mA, 1050 mA
Power Factor	≥0.9 (at full load)
Driver	Constant current, Thermal protected, Voltage regulated, Harmonic filter protection
Surge protection options (kV)	6 Kv (standard) 10 kV (optional) with LED signal and thermo fuse to disconnect load at the end of life 20 kV (optional) with LED signal and thermo fuse to disconnect load at the end of life
Control system	On-off (standard), Bluetooth, DALI, 1-10V DIM, stand alone automation
Main connection	For cable max section 2,5 mm <sup>2</sup> Outgoing cable H05RN-F 2/3/5 x 1,5 mm <sup>2</sup> Length on request.(optional)
Electromagnetic compatibility (EMC)	IEC 61000, EN 55015, IEC 61000-3-2, IEC 61000-4-5, IEC 61547, IEC 61000-3-3, IEC 61000-4-2, IEC 61000-2-2, IEC 61000-4-11, IEC 61643-11

### OPTICAL INFORMATION

LED colour temperature	2700K (warm white), 3000K (warm white), 4000K (neutral white) (standard), 5000K (cool white), 5700K (cool white), 6500K (cool white), Other (amber, blue, green, red)
Colour rendering index (CRI)	CRI ≥70, CRI ≥80 (optional), CRI ≥90 (optional)
Upward light output ratio	0%
Photobiological safety class	IEC 62471, EN 62778 EXEMPT GROUP
Testing standard	LM 79-19 , EN 13032-1 (all measurements in ISO17025 accredited laboratory)
Lifetime of the LEDs	Tq= 25 °, 700 Ma 187.000h - L90B10 Tq= 55 °, 700 Ma 156.000h - L90B10



www.noral.de  
noral@noral.de  
+49 4025 467 12 32

# Compaq NL2006

## Die-Cast Aluminium Housing



Number of Power LED's / Rating / Current	Luminaire Output Flux (lm)		W (mm)	L (mm)	h (mm)	Item / Box	Average Weight (kg)	Order Code	System Lumen / W (lm)	
	max.	min.							max.	min.
24 / 60W - 800 mA	9900	7500	240	387	125	1	2.30	N2006-LED0060NW-ECC	165	125
24 / 70W - 925 mA	11550	8750	240	387	125	1	2.30	N2006-LED0070NW-ECC	165	125
24 / 80W - 1050 mA	13200	10000	240	387	125	1	2.30	N2006-LED0080NW-ECC	165	125
48 / 50W - 350 mA	8250	6250	240	387	125	1	2.30	N2006-LED2050NW-ECC	165	125
48 / 75W - 500 mA	12375	9375	240	387	125	1	2.30	N2006-LED2075NW-ECC	165	125
48 / 90W - 600 mA	14850	11250	240	387	125	1	2.30	N2006-LED2090NW-ECC	165	125
48 / 110W - 700 mA	18150	13750	240	387	125	1	2.30	N2006-LED2110NW-ECC	165	125

Depending on the luminaire configuration. For more details, please contact us.  
Tolerance on LED flux is +/-7% and on total luminaire power +/- 5%.

### Main Applications



Highways & Secondary Roads

Residential Areas

Parks


Car Parks



Environment Lighting & Industrial Areas

Roundabouts

Street and Avenue



[www.noral.de](http://www.noral.de)  
[noral@noral.de](mailto:noral@noral.de)

+49 4025 467 12 32

Noral GmbH reserve the right to modify design and/or production characteristics of their products. photographs and data used in this catalogue are for illustrative purposes are not binding on the company.

The copying or reproduction, in part or in full, of any descriptions, technical data drawings or photographs shown in this catalogue is expressly forbidden.

