



Dynamo NL2065 Solar PV

Die-Cast Aluminium Housing



www.noral.de
noral@noral.de
 +49 4025 467 12 32

GENERAL INFORMATION

Mounting Module	Post top or side entry from 25-45Ø Post top or side entry from 42- 60Ø Post top or side entry from 60-76Ø (optional) Spigot entry 100mm
Mounting Module Tilt Angles	Post top/side entry 0, +5, +10, +15
Operating Temperature	-40°C / +55°C
Storage Temperature	-40°C / +80°C
Glass Mounting Options	Capsule mounting system Tool-free clips system (optional)
LED Modules	Removable / Replaceable optical unit
Lens Options	COL 1030 (standard) Project-specific lens selection
Main Reference	EN 60598-1, EN 60598-2-3, EN 62471, EN 60068-2-11, EN60068-2-52, ISO9227, ASTM B117, ASTM D3359-78, ISO 4628-2, ISO 4628-4, EN 60529, EN 62262, ANSI C136.10-2017, ANSI C136.2-2018, EN 62031, IEC 62384, ASTM D3359, EN ISO 2403, IES LM 80-15, IES LM 82-12, IES LM 84-14, IES LM 85-14, IES TM 21-1, ISO 9001, ISO14001, ISO18001, ISO5001, TURKAK
Company Standards	

HOUSING AND MATERIALS

Housing	Non corrosive high pressure die-cast aluminium
Optic	PMMA or PC
Gasket	Silicon or polyurethane without junction points.
Housing Finish	UNI EN1706 powder painted
Refractor	Tempered glass min. 4mm high transparency UV resistant (optional)
Cable Gland	IP66, Plastic PC9, IP67 (optional), IP68 (optional)
Standard Colour	RAL7021 Metallic
Tightness Level	IP66, IP67 (optional), IP68 (optional)
Impact Housing Resistance	IK10 (20 J)
Impact Glass Resistance	IK08 (5 J), IK09 (optional) (10 J), IK10 (optional) (20 J)
Vibration Test	Compliant with modified IEC 68-2-6 (0.5G), ANSI C136.31 (3G-5G)

ELECTRICAL INFORMATION

Electrical Class	Class I, Class II (optional)	
Nominal Voltage	10-30V, 24V-48V (optional)	
Led Current	350 mA, 500 mA, 700 mA, 925 mA, 1050 mA	
Power Factor	≥0.9 (at full load)	
Smart Solar Charge Controllers	200Wp, 400Wp and 600Wp versions Support Gel and LiFePO4 batteries Offgrid and Hybrid(optional) solar	
Battery Sub System	Gel batteries *12V and 48V *65-250Ah *800 cycles at %70 DOD *IP68 rated	LiFePO4 batteries *12.8V and 25.6V *50-180Ah *2000 cycles at 90% DOD *IP68 rated
PV Panel Sub System	For 12V, 24V and 48V system 30Wp-325Wp flat panel 100-190Wp vertical panel (optional)	
Surge Protection Options (kV)	6 Kv (standard) 10 kV (optional) with LED signal and thermo fuse to disconnect load at the end of life 20 kV (optional) with LED signal and thermo fuse to disconnect load at the end of life	
Control System	On-off (standard), Bluetooth, DALI, 1-10V DIM, stand alone automation	
Socket	NEMA 4-pin (ZHAGA book 18) (optional) NEMA 5-pin (ANSI C136.41) (optional) NEMA 7-pin (ANSI C136.41) (optional)	
Sensor	PIR (optional), Photocell (optional), Daylight (optional)	
Mains connection	For cable max section 2,5 mm2 Outgoing cable H05RN-F 2/3/5 x 1,5 mm2 Length on request.(optional)	
Electromagnetic compatibility (EMC)	IEC 61000, EN 55015, IEC 61000-3-2, IEC 61000-4-5, IEC 61547, IEC 61000-3-3, IEC 61000-4-2, IEC 61000-2-2, IEC 61000-4-11, IEC 61643-11	
OPTICAL INFORMATION		
Led colour temperature	2700K (warm white), 3000K (warm white), 4000K (neutral white) (standard), 5000K (cool white), 5700K (cool white), 6500K (cool white), Other (amber, blue, green, red)	
Colour rendering index (CRI)	CRI ≥70, CRI ≥80 (optional), CRI ≥90 (optional)	
Upward light output ratio	0%	
Photobiological safety class	IEC 62471, EN 62778 EXEMPT GROUP	
Testing standard	LM 79-19, EN 13032-1 (all measurements in ISO17025 accredited laboratory)	
Lifetime of the LED's	Tq= 25 °, 700 Ma 187.000h - L90B10 Tq= 55 °, 700 Ma 156.000h - L90B10	





Dynamo NL2065 Solar PV Die-Cast Aluminium Housing



Number of Power LED's / Rating / Current	Luminaire Output Flux (lm)		W (mm)	L (mm)	h (mm)	Item / Box	Average Weight (kg)	Order Code	System Lumen / W (lm)	
	max.	min.							max.	min.
32 / 35W - 350 mA	5250	4025	215	443	92	1	4.40	N2065-LED2035NW-ECG	150	115
32 / 50W - 500 mA	7500	5750	215	443	92	1	4.40	N2065-LED2050NW-ECG	150	115
32 / 70W - 700 mA	10500	8050	215	443	92	1	4.40	N2065-LED2070NW-ECG	150	115
32 / 95W - 925 mA	14250	10925	215	443	92	1	4.40	N2065-LED2095NW-ECG	150	115
32 / 110W - 1050 mA	16500	12650	215	443	92	1	4.40	N2065-LED2110NW-ECG	150	115

Depending on the luminaire configuration. For more details, please contact us.
Tolerance on LED flux is +/-7% and on total luminaire power +/- 5%.

Main Applications



www.noral.de
noral@noral.de
+49 4025 467 12 32

Cemdag reserve the right to modify design and/or production characteristics of their products, photographs and data used in this catalogue are for illustrative purposes are not binding on the company.

The copying or reproduction, in part or in full, of any descriptions, technical data drawings or photographs shown in this catalogue is expressly forbidden.

